

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. (original) An electronic apparatus comprising:

a body including a first attached body portion and a second attached body portion; and
a terminal protection cover including a first attaching cover portion and a second
attaching cover portion, wherein

after said first attaching cover portion is attached to said first attached body portion, said
second attaching cover portion is rotated around said first attaching cover portion and said
second attaching cover portion is fitted to said second attached body portion.

2. (Original) The electronic apparatus as set forth in claim 1, wherein
said first attached body portion and said second attached body portion are a first opening
and a second opening aligned in a first direction,

said first attaching cover portion and said second attaching cover portion are respectively
a rotational shaft portion to be inserted into said first opening and a cover main portion to be
fitted into said second opening, and

after said rotational shaft portion is inserted into said first opening, said cover main
portion is rotated around said rotational shaft portion and said cover main portion is fitted into
said second opening.

PRELIMINARY AMENDMENT

New U.S. National Stage Entry of PCT/JP2005/002518

3. (Original) The electronic apparatus as set forth in claim 2, wherein
said first opening is an oval having its longitudinal direction in a second direction,
said second opening is a rectangular having its longitudinal direction in said first
direction,

said rotational shaft portion includes a cylindrical shaft and a hook at the distal end of
said shaft,

said cover main portion has a shape to be fitted into said second opening, and
after said shaft and hook are inserted into said oval opening, said cover main portion is
rotated around said shaft and said cover main portion is fitted into said rectangular opening.

4. (Original) The electronic apparatus as set forth in claim 3, wherein
said hook includes a tongue-shaped piece and a protrusion in the longitudinal direction of
said cover main portion, with said shaft intervening therebetween.

5. (Original) The electronic apparatus as set forth in claim 3, wherein
said hook includes a tongue-shaped piece and a protrusion in the longitudinal direction of
said cover main portion, with said shaft intervening therebetween, and
two small protrusions arranged in a direction perpendicular to the longitudinal direction
of said cover main body, with said shaft intervening.

6. (Original) The electronic apparatus as set forth in any of claims 1 to 5, wherein
said terminal protection cover is made from elastic material.

PRELIMINARY AMENDMENT

New U.S. National Stage Entry of PCT/JP2005/002518

7. (Original) The electronic apparatus as set forth in any of claims 1 to 5, in which one portion of said second attaching cover portion is cut away according to a shape of said first attached body portion.

8. (Original) The electronic apparatus as set forth in claim 7, wherein by cutting away one portion of said second attaching cover portion, said second attaching cover portion is tapered.

9. (Currently Amended) The electronic apparatus as set forth in claim 7 ~~or claim 8~~, wherein

a rib extending toward a direction of the inner diameter is provided in said first attached body portion at the inner portion corresponding to said first attaching cover portion.

10. (Original) The electronic apparatus as set forth in claim 9, wherein said rib is formed into a shape having an inclined cross section tapering inwardly from the outside of said body.

11. (Currently Amended) A mobile phone to which the electronic apparatus as set forth in any of claims 1 to 5 ~~1 to 10~~ is applied.

PRELIMINARY AMENDMENT

New U.S. National Stage Entry of PCT/JP2005/002518

12. (Original) A method of attaching a terminal protection cover for an electronic apparatus which comprises

a body including an oval opening having its longitudinal direction in a second direction and a rectangular opening having its longitudinal direction in a first direction, which openings are aligned in said first direction, and

a terminal protection cover rotatable and including a rotational shaft portion having a hook at the distal end of a cylindrical shaft and a cover main portion formed into a shape to be fitted into said rectangular opening,

the method comprising the steps of:

a step of inserting said rotational shaft into said oval opening, and

a step of rotating said cover main portion around said rotational shaft and fitting said cover main portion to said rectangular opening.